TRACTOR **540 XT**

HIGHEST TORQUE OF THE CATEGORY

Tractor Agrale 540 XT has a 40 hp engine. Versatile, robust and economical, it is ideal for use in small properties and in densified





www.agrale.com.br

- 4-cylinder engine
- Gears Inverter as standard
- Reduced dimensions, ideal for use in densfied crops
- Lifting capacity of 1,100 kg








TRACTOR 540 XT

ENGINE	
Brand / model	AGRALE
No. of Cylinders	04/ 2.417 cm
Aspiration	Natural
Power	40 cv (29,4 kW) @ 2.400 rpm
Maximum Torque	15,2 kgf.m (14,9 N.m) @ 1.600 rpm
DRIVING TRANSMISSION	13,2 kgi.iii (14,3 N.iii) @ 1.000 ipiii
Type	Syncro Shuttle
No. of Gears	8 forward and 8 reverse
Differential lock	Mechanical foot pedal and automatic
	disengaging
Front axle	Center differential (4WD)
CLUTCH	
Туре	Double dry disc
Drive	Mechanical
POWER TAKEOFF	
Drive	Mechanical
Type / drive	Independent
Nominal Speed	540 rpm @ 2.077 engine rpm
HYDRAULIC SYSTEM	
Pressure	180 kgf/cm
Maximum Flow	36 L/min @ 2.400 rpm
Remote control	Optional
Hitch	3 Points - Category I
Lift capacity	1100kg

BRAKES		
Service Brake	Wet disc oil bath	
Parking Brake	Manual lever	
STEERING WHEEL		
Туре	Hydrostatic	
WHEELSETS		
Standard Front Tires	250/80x18R1	
Standard Rear Tires	12.4x24R1	
Optional Weelsets	7.5Lx15R1	
	9.50x24R1	
	11.2x24R1	
ELECTRIC SYSTEM		
Battery	12V 55Ah	
Alternator	14V 55A	
CAPACITIES		
Fuel Tank	44 L	
DIMENSIONS		
Width	1.365 mm minimum	
WEIGHTS		
Shipping weight	1.850 kg	
Operating weight (curb	2.140 kg	
weight)	2.140 kg	
OPTIONAL ITEMS		
Front guard,		
Front weights (4, 6 or 8),		
Rear wheels weights, Rear light,		
Lower steering column, Lower seat,		
Reinforced draw bar,		
Single or Double valve remote control.		

INVERSOR 8X8 (MOTOR A 2400RPM - PNEUS STANDARD)





Double hydraulic command with cabin.

