TRACTOR 4233





www.agrale.com.br

- Better performance and safety in steep areas
- 4WD Traction







TRACTOR 4233

ENGINE	
Brand / model	Agrale M790
No. of Cylinders	2 / 1270 cm
Aspiration	Natural
Power	30 CV (22 KW) @ 3.000 rpm (NBR ISO 1585)
Maximum Torque	6,9 daNm - 7,0 kgf.m @ 2.550 rpm (NBR ISO 1585)
DRIVING TRANSMISSION	
Туре	Mechanical, with sliding gears
No. of Gears	8 Front/ 4 Reverse
Differential lock	Mechanical foot pedal and automatic disengaging
Front axle	Combined with the transmission
CLUTCH	
Туре	Simple dry disc
Drive	Mechanical
POWER TAKEOFF	
Drive	Mechanical
Type / drive	Dependent
Nominal Speed	540 rpm at 2.600 rpm (engine) or ground PTO
HYDRAULIC SYSTEM	
Pressure	120 kgf/cm
Maximum Flow	24 L/min @ 3.000 engine rpm
Remote control	2 way single command
Hitch	Cat I
Lift capacity	1050kg

BRAKES		
Service Brake	Rear Drum Brake	
Parking Brake	Manual lever	
STEERING WHEEL		
Туре	Hydrostatic	
WHEELSETS		
Standard Front Tires	7,50L x 15 R1	
Standard Rear Tires	7,50 x 15 R1	
ELECTRIC SYSTEM		
Battery	12V 55 A.h	
Alternator	14V 55 A	
CAPACITIES		
Fuel Tank	35 L	
DIMENSIONS		
Width	1.120 / 1.280 mm	
WEIGHTS		
Shipping weight	1.080 kg	
Operating weight (curb weight)	1.300 kg	
OPTIONAL ITEMS		
License plate kit and reverse light		

STANDARD 8X4 (MOTOR A 3000RPM - PNEUS STANDARD)



