TRACTOR 4100

THE MOST ECONOMICAL TRACTOR OF THE CATEGORY

Tractor 4100 has small dimensions and excellent performance, outstanding for operational economy. A fundamental model in the smallholder agricultural mechanization.



www.agrale.com.br

- Available in 4x2 and 4x4 versions
- Unbeatable in terms of economy
- In uninterrupted production for more than 50 years




TRACTOR 4100

| ENGINE | | |
|----------------------|------------------------------------|--|
| Brand / model | AGRALE M 93 ID | |
| No. of Cylinders | 1/ 668 cm | |
| Aspiration | Natural | |
| Power | 15 HP @ 2.750 rpm | |
| Maximum Power in PTO | 13,2 HP (9,7 kW) @ 2.750 rpm | |
| Maximum Torque | 3,9 daNm - 4,0 kgf.m @ 2.350 rpm | |
| DRIVING TRANSMISSION | | |
| Туре | Mecanic | |
| No. of Gears | 7 Front / 3 Forward | |
| Differential lock | Mechanical by hand lever | |
| Front axle | Oscilating and adjustable / Center | |
| | differential (4WD) | |
| CLUTCH | | |
| Туре | Simple dry disc | |
| Drive | Mechanical | |
| POWER TAKEOFF | | |
| Drive | Mechanical | |
| Type / drive | Mechanical | |
| Nominal Speed | 1.000 rpm @ 2.750 engine rpm (4th | |
| | and low range) | |
| HYDRAULIC SYSTEM | | |
| Pressure | 120 kgf/cm | |
| Maximum Flow | 23,65 L/min @ 2.750 engine rpm | |
| Remote control | (Optional) 2 way single command | |
| Hitch | 3 Points - Agrale special category | |
| Lift capacity | 440 kg @ 610 mm behind lift point | |
| | | |

| BRAKES | |
|--|-----------------------|
| Service Brake | With expandable shoes |
| Parking Brake | Manual Lever |
| STEERING WHEEL | |
| Туре | Hydrostatic |
| WHEELSETS | |
| Standard Front Tires | 4.00 15" / 6.5/80 12" |
| Standard Rear Tires | 8.3/8 24" |
| Optional Weelsets | Garden tires |
| ELECTRIC SYSTEM | |
| Battery | 12V 55 A.h |
| Alternator | 14V 55 A |
| CAPACITIES | |
| Fuel Tank | 19,6 L |
| DIMENSIONS | |
| Height | 1220 mm |
| Front gauge | 797 mm / 925 mm (2wd) |
| | 910 mm (fixed) (4wd) |
| Rear Tread | 863 mm / 976 mm |
| Length | 2.450 mm |
| Width | 1187 mm/ 1.200 mm |
| WEIGHTS | |
| Shipping weight | 1120 kg / 1140 kg |
| Operating weight (curb | 1160 kg / 1260 kg |
| weight) | |
| OPTIONAL ITEMS | |
| Front wheels counterweights, Rear whels weights, Front counterweight (under the engine), Simple hydraulic control. | |

STANDARD 7X3 (MOTOR A 2750RPM - PNEUS STANDARD)







This literature is for the product information and ilustration only, and Agrale, or the Bidder, are able to offer its products with characteristics or different optional informed here in, valid for both, as final document for the offer, the Commercial Proposed celebrated by the legal representative of the company.